












Material: Tabla de otel 0,43 mm grosime, galvanizata cu aliaj aluminiu-zinc pe ambele fete.

La exterior: Vopsire in camp electrostatic in variante satin si gloss.

La interior: Strat poliesteric de protectie, aprox. 500 g / mp.

Unghi			
Unghi minim	10°	Unghi maxim	90°
Dimensiuni			
Dimensiuni efective	1324 mm x 410 mm	Dimensiuni utile	1260 mm x 370 mm
Distanta de latuire	370 mm	Acoperire utila liniara	1260 mm
Acoperire pe modul	0,46 mp / modul	Numar de module / mp	2,145 module / mp
Greutate			
Greutate pe mp	5,47 Kg / mp	Greutate pe modul	2,55 Kg / modul
Fixare			
Cuie pentru fixare	Cuie Decra galvanizate si acoperite, 50 mm x 2,5 mm <i>(Disponibile pentru ciocan sau pistol de cuie)</i>		
Numar de cuie pe modul	4 cuie pe modul		
Lati (sipca)			
Necesar sipca	2,7 ml pe mp de invelitoare (plus pierderi)		
Recomandari de montaj			
Forme simple ale apei	Montarea modulelor unul sub celalalt		
Forme complexe ale apei	Montarea decalata a modulelor (in zig-zag)		
Coduri produs, culori			
Cod produs	16xxS <i>("xx" reprezinta codul culorii format din 2 cifre)</i>		
High Gloss	Satin	Cool Roof	Dry Roof
 Gloss Black	 Satin Graphite	 Cool Black	 Dry Black
 Gloss Bordeaux	 Satin Terracotta	 Cool Terracotta	 Dry Terracotta
 Gloss Green	 Satin Mocca	 Cool Mocca	 Dry Mocca